

**SEGULA****SUPERB KINGDOM LIMITED**

Room7A, 9/F., Block B, Hong Kong Industrial Centre  
 489-491 Castle Peak Road, Lai Chi Kok, Kowloon, Hong Kong  
 Telephone: (+852) 3954 5598

<b>Lighting Type:</b>	Bulb	<b>Lamp:</b>	LED Golfball Frosted
<b>Manufacturer:</b>	SEGULA	<b>Catalog No:</b>	50322
<b>Location:</b>			

**LED Golfball Frosted****Product Feature**

- \* Precision German Engineering
- \* Segula Constant Current Algorithm
- \* 1%-100% Smooth Dimming
- \* No Shadow, No Flickering
- \* 100% Sapphire Substrate
- \* High Lumen Efficiency
- \* Excellent Heat Dissipation, Low Working Temperature

**Description**

Dimension:  $\phi$ 45mm\*80mm

Input Voltage: AC220-240V 50-60Hz

Color Temp: 2600K

CRI: 90 Ra

Power Factor: >95%

Finishing: Frosted

MacAdam: 3 Step

**Warranty**

Module: 2 Years

Item No	Socket	Energy Used(W)	Lumen	Color Temp	CRI	Beam Angle	Dimmable	Energy Class
50322	E14	3.5W	230lm	2600K	90 Ra	180°	Yes	A+

# SEGULA

## SUPERB KINGDOM LIMITED

Room7A, 9/F., Block B, Hong Kong Industrial Centre  
489-491 Castle Peak Road, Lai Chi Kok, Kowloon, Hong Kong  
Telephone: (+852) 3954 5598

<b>Lighting Type:</b>	Bulb	<b>Lamp:</b>	LED Candle Bulb Clear
<b>Manufacturer:</b>	SEGULA	<b>Catalog No:</b>	50313L
<b>Location:</b>			

## LED Candle Bulb Clear



### Product Feature

- \* Precision German Engineering
- \* Segula Constant Current Algorithm
- \* 1%-100% Smooth Dimming
- \* No Shadow, No Flickering
- \* 100% Sapphire Substrate
- \* High Lumen Efficiency
- \* Excellent Heat Dissipation, Low Working Temperature

### Description

Dimension:  $\phi 35 \times 98 \text{mm}$

Input Voltage: AC220-240V 50-60Hz

Color Temp: 2600K

CRI: 90 Ra

Power Factor: >95%

Finishing: Clear

Optional: Dimmable

MacAdam: 3 Step

### Warranty

Module: 2 Years

Item No	Socket	Energy Used(W)	Lumen	Color Temp	CRI	Beam Angle	Dimmable	Energy Class
50313L	E14	4W	300lm	2600K	90 Ra	360°	Yes	A+

# Light Source

## Golden Aurora® Filaments



### PRODUCT DESCRIPTION

360-degree Three-dimensional Light Source

High Light Efficiency, High Mechanical Strength, High Reliability

Integrated High Voltage Drive

SNSI / ERP Color Tolerance Standard

Lead-free Package, in Line with ROHS, LM-80 Certification

### FEATURES

- \* 100% Sapphire Substrate Packaging
- \* Industry-Compatible Size: 38\*1.7\*1.8mm
- \* Available Length: 28mm, 38mm, 60mm
- \* Flux Binned at 25°C, chromaticity Binned at 85°C
- \* 90CRI Available for all CCTs

### PRODUCT SUMMARY

Product	Power Class	Test Temperature	Test Current	Typical Forward Voltage	2200K 90CRI		2700K 90CRI		Maximum Current
					Typical Flux	Typical Efficacy	Typical Flux	Typical Efficacy	
38L24FQ	0.66W	25°C	10mA	66-68V	75Lm	120LPW	85Lm	135LPW	13mA