

SEGULA

SUPERB KINGDOM LIMITED

Room7A, 9/F., Block B, Hong Kong Industrial Centre
489-491 Castle Peak Road, Lai Chi Kok, Kowloon, Hong Kong
Telephone: (+852) 3954 5598

Lighting Type:	Bulb	Lamp:	LED A60 Bulb Frosted
Manufacturer:	SEGULA	Catalog No:	50335
Location:			

LED A60 Bulb Frosted



Product Feature

- * Precision German Engineering
- * Segula Constant Current Algorithm
- * 1%-100% Smooth Dimming
- * No Shadow, No Flickering
- * 100% Sapphire Substrate
- * High Lumen Efficiency
- * Excellent Heat Dissipation, Low Working Temperature

Description

Dimension: ϕ 60mm*106mm

Input Voltage: AC220-240V 50-60Hz

Color Temp: 2600K

CRI: 90 Ra

Power Factor: >95%

Finishing: Frosted

MacAdam: 3Step

Warranty

Module: 2 Years

Item No	Socket	Energy Used(W)	Lumen	Color Temp	CRI	Beam Angle	Dimmable	Energy Class
50335	E27	8W	720lm	2600K	90 Ra	360°	Yes	A+

SEGULA

SUPERB KINGDOM LIMITED

Room7A, 9/F, Block B, Hong Kong Industrial Centre
489-491 Castle Peak Road, Lai Chi Kok, Kowloon, Hong Kong
Telephone: (+852) 3954 5598

Lighting Type:	Bulb	Lamp:	LED Candle Bulb Frosted
Manufacturer:	SEGULA	Catalog No:	50323
Location:			

LED Candle Bulb Frosted



Product Feature

- * Precision German Engineering
- * Segula Constant Current Algorithm
- * 1%-100% Smooth Dimming
- * No Shadow, No Flickering
- * 100% Sapphire Substrate
- * High Lumen Efficiency
- * Excellent Heat Dissipation, Low Working Temperature

Description

Dimension: $\phi 35 \times 98 \text{mm}$

Input Voltage: AC220-240V 50-60Hz

Color Temp: 2600K

CRI: 90 Ra

Power Factor: >95%

Finishing: Frosted

Optional: Dimmable

MacAdam: 3Step

Warranty

Module: 2 Years

Item No	Socket	Energy Used(W)	Lumen	Color Temp	CRI	Beam Angle	Dimmable	Energy Class
50323	E14	5W	340lm	2600K	90 Ra	360°	Yes	A+

Light Source

Golden Aurora® Filaments



PRODUCT DESCRIPTION

360-degree Three-dimensional Light Source

High Light Efficiency, High Mechanical Strength, High Reliability

Integrated High Voltage Drive

SNSI / ERP Color Tolerance Standard

Lead-free Package, in Line with ROHS, LM-80 Certification

FEATURES

- * 100% Sapphire Substrate Packaging
- * Industry-Compatible Size: 38*1.7*1.8mm
- * Available Length: 28mm, 38mm, 60mm
- * Flux Binned at 25°C, chromaticity Binned at 85°C
- * 90CRI Available for all CCTs

PRODUCT SUMMARY

Product	Power Class	Test Temperature	Test Current	Typical Forward Voltage	2200K 90CRI		2700K 90CRI		Maximum Current
					Typical Flux	Typical Efficacy	Typical Flux	Typical Efficacy	
38L24FQ	0.66W	25°C	10mA	66-68V	75Lm	120LPW	85Lm	135LPW	13mA